

1 2 3 4

REVISIONS

Rev.	Description	Date	Approved by
01	Initial revision	Oct 09, 2014	Mikhail Novikov

### ORIGINAL WIRING FOR 100/120V MAINS

### WIRING FOR 220/240V MAINS

**WARNING: TO PREVENT ELECTRIC SHOCK DO NOT OPEN THE AMPLIFIER UNTIL POWER SUPPLY CORD PLUG IS COMPLETELY DISCONNECTED FROM THE AC MAINS RECEPTACLE.**

**NOTE: DO NOT USE 240V setting in countries with 220V or 230V AC mains. This will significantly reduce vacuum tubes lifetime due to cathode poisoning as a result of low heater voltage.**

Furthermore, in this case tubes will work under sub-optimal operating conditions, which will degrade overall amplifier performance.

**NOTE:** Be sure to replace SW1 with a similar switch rated at 250V 10A. It is **STRICTLY** prohibited to use the amplifier on 220/240V AC mains with the original power switch due to risk of fire or electric shock.

Responsible dept. R&D	Technical reference Dmitry Novikov-Dragan	Created by Dmitry Novikov-Dragan	Approved by Mikhail Novikov	
		Document type Schematic diagram	Document status Working draft	
		Title, Supplementary Title M-7A dual mono power amplifier Transformer wiring for 220/240V mains		Identification number PF-M7A-00003
		Rev. 01	Date of issue Oct 09, 2014	Lang. EN

1 2 3 4